


SECTION.A-A



SECTION.B-B

PART NO.  
TR150360151200

产品代码TR:Terminal简写  
产品间距:2.00mm  
00: 预留码  
2: 表示卷装  
36:带内扣端子  
51:镍底,整体镀亮锡  
01:磷铜C5191

NOTE :

- MATERIAL SPECIFICATION,
  - CONTACT MATERIAL: PHOSPHOR BRONZE
- TERMINAL PLATING: UNDER PLATING NI 30u"MIN OVER ALL,TIN PLATING 60u"MIN AT CONTACT AREA.
- ELECTRICAL PERFORMANCE,
  - RATED VOLTAGE ;AC/DC,50V
  - ALLOWABLE CURRENT(MAX.) AND APPLICABLE WIRES ;2.0A(24AWG),1.5A(26AWG),1.0A(28AWG), ( $\phi 0.78 \sim \phi 1.28\text{mm}$ )Insulation O.D.
  - DIELECTRIC STRENGTH:500V AC FOR 1 MINUTE,
  - CONTACT RESISTANCE: 20m $\Omega$  MAX.
  - INSULATION RESISTANCE:DC 500V/100 M $\Omega$  MIN.
  - AMBIENT TEMPERATURE RANGE:-40°C~+125°C
  - STORAGE TEMPERATURE: -25°C~+85°C. 70%R.H.MAX. (NO CONDENSATION)
- COMPLIANT WITH RoHS

| GENERAL TOLERANCE |       |       | UNITS |
|-------------------|-------|-------|-------|
| SELECT            |       | √     | mm    |
| TOL.              | 1     | 2     | MAT'L |
| ON.               | ±0.10 | ±0.15 | ±0.20 |
| X.XXX             | ±0.15 | ±0.25 | ±0.25 |
| X.XX              | ±0.20 | ±0.35 | ±0.30 |
| X.X               | ±0.25 | ±0.30 | ±0.50 |
| X.                | ±2'   |       | Q'TY  |
| ANGLE             |       |       |       |

|                        |                |
|------------------------|----------------|
| NAME(INTENDED USE)     | 1.50 带内扣绑线端子   |
| PART NO.(INTENDED USE) | TR150360151200 |
| APPD:                  |                |
| CHKD:                  |                |
| DR:                    | TOM            |

|  |       |      |  |
|--|-------|------|--|
| <b>ATOM</b> ®深圳市爱特姆科技有限公司<br>SHENZHEN ATOM TECHNOLOGY CO.,LTD. |       |      |  |
| TITLE: CUSTOMER DRAWING FOR 1.50mm带内扣绑线端子                      |       |      |  |
| DWG NO.: ATOM-A09654   |       |      |  |
| SCALE  | SHEET | REV. |  |
| 1:1  | 1/1   | A0   |  |